Infitek

BALANCES

Infitek Infitek Infitek Infitek Infitek

Infitek

Infitek Co., Ltd.

TEL: +86-531-88982330
FAX: +86-531-88983691
Website: infitek.com
Email: info@infitek.com
Service: support@infitek.com
Address: Room 201, Building A, No.1 Qianwan 1st Road, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen (Settled in Shenzhen Qianhai Business Secretary Co., Ltd.)

US Office

INFITEK INC.

522W RIVERSIDE AVE STE N,SPOKANE,WA 99201
EMAIL: INFO@INFITEK.COM



VERSION.26

0.01g Precision Balance

BP-212-2C BP-312-2C BP-612-2C
BP-1102-2C BP-2102-2C BP-3102-2C

Description

- LCD/AC and DC power supply
- Tare function/Counting/Unit conversion (g/ct/oz)...
- Min weighing set
- Overload alarm/Level indicator
- Option:Dual display/Interface/Printer/Windproof



Specifications

Model	BP-212-2C	BP-312-2C	BP-612-2C	BP-1102-2C	BP-2102-2C	BP-3102-2C
Max. capacity(g)	210	310	610	1100	2100	3100
Cal.weight	200	200	200	500	Optional	Optional
Readability(g)	0.01					
Repeatability(g)	±0.02					
Liner(g)	±0.03					
Stable Time	≤2s					
Pan Size	Φ130mm					
Operation temp	5-25℃					
Option	Printer, RS232, Weight					
Outline size	270x195x85mm					
Package Dimension (W*D*H)(mm)	330*260*200mm					
Ten Packing Size	660x470x320					
N.W.(kg)	Unit set 2.5kg/Ten 25kg					
G.W.(kg)	Unit set 3kg/Ten 30kg					

0.01g Precision Balance

BP-3002-C BP-4002-C BP-5002-C

Description

- LCD
- Tare function/Counting
- Overload alarm/Level indicator
- Option:Printer
- Aluminum shell/ Unit conversion(g/ct/oz)...





Specifications

Model	BP-3002-C	BP-4002-C	BP-5002-C
Max. capacity(g)	3000g	4000g	5000g
Readability(g)	0.01		
Min weighing(g)	0.04		
Stable Time	≤3s		
Display	LCD		
Pan size	180x180mm		
Operation temp	5-25℃		
Repeatability	±0.02g		
Linearity	±0.03g		
Option	Printer		
N . weight	5kg		
Package Dimension(W*D*H)(mm)	420*320*430mm		