Infitek

BALANCES

Infitek Infitek Infitek Infitek Infitek

Infitek

Infitek Co., Ltd.

TEL: +86-531-88982330
FAX: +86-531-88983691
Website: infitek.com
Email: info@infitek.com
Service: support@infitek.com
Address: Room 201, Building A, No.1 Qianwan 1st Road, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen (Settled in Shenzhen Qianhai Business Secretary Co., Ltd.)

US Office

INFITEK INC.

522W RIVERSIDE AVE STE N,SPOKANE,WA 99201
EMAIL: INFO@INFITEK.COM



VERSION.26

0.0001g Analytical Balance

BA-W1004 BA-W1204 BA-W2004 BA-W2204

Description

- Aluminum shell Large space wind proof cover
- LCD(White back light with black font)
- Tare function/Counting/Unit conversion(g/mg/ct/oz)...
- Electromagnetic sensor
- Sensitivity/Speed set/ Percentage
- Overload alarm/Fault alarm/Level indicator
- Option:Under weighing/Printer



Specifications

Model	BA-W1004	BA-W1204	BA-W2004	BA-W2204
Capacity(g)	100	120	200	220
Resolution(g)	0.0001			
Min Weighing(g)	0.0004			
Stable Time	≤3s			
Display	LCD（white back light with black font）			
Pan Size	Φ80mm			
Operation Temp	5-35℃			
Repeatability	±0.0002g			
Liner	±0.0003g			
Draft Shield Size	240mmx190mmx265mm			
Communication	RS232(Standard)			
Calibration	External Calibration			
Cal.weight	100g		200g	
Option	Printer/Under weighing			
Package Dimension(W*D*H)	Inside: 415x285x430mm Outside: 530*390*540mm			
Gross Weight	10kg			

0.0001g Analytical Balance

BA-N1104 BA-N1204 BA-N2004 BA-N2204

Description

- Internal auto calibration
- Under weighing
- Unit conversion (g/mg/ct/oz)...
- Aluminum shell/Large space wind proof cover
- Tare function/ Counting/Percentage
- Sensitivity/Speed set
- Electromagnetic force sensor
- LCD(White back light with black font)
- One key/Time trigger internal calibration
- Overload alarm/Fault alarm/Level indicator



Specifications

Model	BA-N1104	BA-N1204	BA-N2004	BA-N2204
Max. capacity(g)	110	120	200	220
Readability(g)	0.0001			
Min weighing(g)	0.0004			
Stable Time	≤3s			
Display	LCD（white back light with black font）			
Pan size	Φ80mm			
Operation temp	5-25℃			
Repeatability	±0.0002g			
Linearity	±0.0003g			
Draft shield size	240mmx190mmx265mm			
Cal.weight	Internal Calibration			
Option	RS232(Standard)			
Package Dimension(W*D*H)(mm)	530*390*530			
N.W./G.W.(kg)	8/10.2kg			