Infitek

BALANCES

Infitek Infitek Infitek Infitek Infitek

Infitek

Infitek Co., Ltd.

TEL: +86-531-88982330
FAX: +86-531-88983691
Website: infitek.com
Email: info@infitek.com
Service: support@infitek.com
Address: Room 201, Building A, No.1 Qianwan 1st Road, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen (Settled in Shenzhen Qianhai Business Secretary Co., Ltd.)

US Office

INFITEK INC.

522W RIVERSIDE AVE STE N,SPOKANE,WA 99201
EMAIL: INFO@INFITEK.COM



VERSION.26

Halogen Moisture Analyzer

MCA110-10 MCA110-5 MCA110-2 MCA110-1A





Description

- Halogen lamp/HBM sensor
- The percentage of moisture content/dry residual
- Aluminum shell/Stainless steel chamber
- Store historical set
- LCD(White back light with black font)
- Option:Aluminum box/Printer/Grinder
- Temperature/Time set

Product details





Specifications

Model	MCA110-10	MCA110-5	MCA110-2	MCA110-1A
Capacity	110g			
Readability	0.01g	0.005g	0.002g	0.001g
Operating Temp	5℃-35℃			
Display	Backlit LCD			High Definition Backlit LCD
Calibration	External Calibration			
Interface	RS232(Standard)			
Pan Size	Ø90mm			
Heating Source	Halogen Lamp-1			Halogen Lamp-2
Temp. Sensor	PT100			
Temp. Range	40℃-199℃			
Temp. Step	1℃			
Moisture Range	0.00%-100.00%			
Moisture Readability	0.20%	0.10%	0.04%	0.01%
Dry Range	100.00%-0.00%			
Dry Readability	0.20%	0.10%	0.04%	0.01%
Temp Setting	40℃-199℃ By 1℃ Step			
Time Setting	1-99min By 10s			
Number of Storage	15			
Heater	220V ±15% 50Hz/110V±15% 60Hz/400W			
Balance	Input: 220V 50Hz/110V 60HZ Output: 9V			
Chamber Height	22mm			
External Dimension(W*D*H)(mm)	280*250*180			
N.W.(kg)	5.8			
Package Dimension (W*D*H)(mm)	500*460*370			
G.W.(kg)	7.1			