HCUS-400 Ultrasonic Level Transmitter-Standard



Application	Liquids
Measuring Range	0～20m
Connection Process	Thread、Plastic flange
Process Pressure	≤0.3MPa
Accuracy	0.5%-1.0%
Protection Grade	Display Meter IP67/Probe IP68
Signal Output	(4-20)mA/RS485Modbus





Type	Code	Parameters		
Sensor Type	P	Standard	T	Anti-Corrosion Type
Housing/ Protection Grade	L	Die-casting aluminium/Single chamber/IP67		
	G	Die-casting aluminium/Dual chamber housing/IP67		
	S	Plastic housing IP/66		
	D	Stainless steel / IP68		
Probe Mounting Size	G	Thread G1.5,Rated Range 5m		
	H	Thread G2,Rated Range 5m,10m		
	J	Thread M78*2,Rated Range 15m		
	K	Thread M78*2,Rated Range 20m		
	Y	Special Custom		
Power Supply	A	220 V AC		
	D	24V DC		
	Y	Special Custom		
Output Mode	I	(4-20)mA Two-Wire System (Without Relay Output)		
	K	(4-20)mA Four-Wire		
	O	485 Communication (MODBUS-RTU protocol)		
	M	(4~20)mA+485 Communication (MODBUS-RTU)		
	N	(4~20)mA Two-Wire HART Bus		
	Y	Special Custom		
Relay Output	R	No Relay Output		
	R1	1 Relay		
	R2	2 Relays		
Electrical Interface	M	M20*1.5		
	Y	Special Custom		
Sensor Range	XXX	Unit : m		
Process Connection	G	Thread G1.5	H	Thread G2
	K	Thread M78*2	M	Thread G3
	A	Flange DN50	J	Flange DN65
	B	Flange DN80	C	Flange DN100
	Y	Special Custom		
Special Custom	X	Special Custom		