HCUS-600 Ultrasonic Level Transmitter-Separated Type



Application	Liquids
Measuring Range	0～30m
Connection Process	Thread
Process Pressure	≤0.3MPa
Accuracy	0.5%-1.0%
Protection Grade	Display Meter IP67/Probe IP68
Signal Output	(4-20)mA Four-Wire/RS485 Modbus





Type	Code	Parameters
Instrument Type	P	Conventional
	T	Anti-Corrosion Type
Housing/ Protection Grade	S	Plastic shell
Probe Mounting Size	G	Thread G1½,Rated Range 5m
	H	Thread G2,Rated Range 10m
	J	Thread M78*2,Rated Range 20m
	K	Thread M78*2,Rated Range 30m
	Y	Special Custom
Power Supply	A	AC Supply （85~265） V AC
	D	DC Supply 24V DC
Output Mode	K	(4-20)mA
	M	(4-20)mA、RS485Modbus
	Y	Special Custom
Relay Output	R	No Relay Output
	R1	1 Relay
	R2	2 Relays
	R3	3 Relays
	R4	4 Relays
Electrical Interface	N	M18*1.5 Waterproof Cable Gland
Sensor Range	XXX	05、10、15、20、30
Probe Cable	XXX	Unit : m
Special Custom	X	Special Custom